


CROSS CREEK LANTERN

Arts and crafts style in a path light for distinctive simplicity. Matching 120V surface and post mount styles available.

15322 AGZ - Aged Bronze

Cast Aluminum with textured linen seeded glass panels

12V T5 wedge base socket 

16.25-W(VA) 921X (17025) Xenon light source
Power usage at 12V AC input
VA MAX: 16.25-W(VA)

11.6-W(VA) 921X (17023)
6.5-W(VA) 918X (17022)
4-W(VA) 901X (17021)

2W (18039-18041) see page 159
Compares up to 16W Xenon

35" of usable #18-2, SPT-1-W leads
Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange
15607 - Surface Mounting Bracket

U.S. Patent No. D580,084

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
---------------------	----	----	----	----	----	----	----	----	----

Footcandles	3.2	1.2	.26	-	-	-	-	-	-
-------------	-----	-----	-----	---	---	---	---	---	---



**EASILY CONVERTED
TO LED WITH THE
APPROPRIATE BULB**

WT322



Hybrid Path & Spread

Let stylish design and durable construction light the way.

Enhance The Night - www.landlight.ca