

SEED SEAL WIRE CONNECTOR

Speed Seal™
WATERPROOF WIRE CONNECTORS

Silicone injected Speed Seal Waterproof Connectors are for use on irrigation valves and low voltage lighting.

FEATURES AND BENEFITS

- **Metal Helical Insert**—Twists wires together (no pre-twisting required) and securely locks them into place when twisted in a clockwise direction (capable of 80# torque).
- **Ergonomic Grip**—Increases rapid turn capability and provides comfort and low hand stress.
- **High Density Material**—For extended use and reliability.

OPERATING RANGE

- **Maximum Voltage:** 600V maximum building wire (1000 max. signs or lumenaries)
- **Wire Type:** Copper/Copper

SPECIFICATIONS

- **Dimensions:**
 - Orange Connector Size: 27/32" X 7/16"
 - Orange Wire Range: Min. #22 to Max. #12
 - Blue Connector Size: 17/32" X 15/16"
 - Blue Wire Range: Min. #22 to Max. #12
 - Tan Connector Size: 13/16" X 19/16"
 - Tan Wire Range: Min. #22 to Max. #6
- **Temperature Rating:** 221°F (105°C)
- **Silicon Sealant Temperature:** -45°F to 400°F



WTHR-ORANGE

WTHR-BLUE

WTHR-TAN



LandLight
Enhance The Night

Enhance The Night - www.landlight.ca